









LG-330-TT	AVAILABLE WIDTH: 330MM/420MM/520MM
Max Web Width	330mm
Max Die-cutting Speed	120 m/min
Max Die-cutting length	190.5-647.7mm
Max Unwinder dia.	700mm
Max Rewinder dia.	400mm
Min Slitting width	16mm
Accuracy of Adhesive Cutting	±0.15mm
Registration	Mark Sensor
Slitting Blades installed	6 sets
Air Supply	0.4~0.6MPa
Total Motor Power	16.5KW
Dimension	4150×1500×1890mm
Weight	2000KGS

<sup>\*</sup> May vary depending on selected options&configurations



RHYTUAN

# **UNWINDER & WEB GUIDING**

Servo driven unwind for clock wise and anti-clock wise unwinding. Automatic tension control, end-of-roll detection, webquide, integrated splice table, 76mm unwind mandrel. Factory upgrade to unwind rolls with dia = 1000mm and a reel lift possible.

> Double Die Cutting Station

### **DOUBLE STATION** ROTARY DIE CUTTER

Servo-driven, double station full rotary die cutter with solid cylinder exchange. Offers high speed and high accuracy die cutting.



## **CONTROL PANEL**

Intuitive touch screen interface, mounted on sliding rail for easy control of machine and vision





Full Rotary

Die Cutting Machine For

Blank Labels

### **REWINDING OPTIONS**

Standard turret rewind and one more single rewind for optimal productivity.

## **SLITTING OPTIONS**

Optional standard 6 shear slitter or razor blade slitter. Easy to install. Features a standard high pressure waste suction



High Accuracy Converting In Speeds Of Up To 120 m/min.