

TOP-330-PLUS | VARNISHING & DIE CUTTING SOLUTION



Machine for cost-efficient, high quality converting and finishing. Features winding, cold foiling, super varnishing, flexo printing, semi- or full rotary die cutting, IML system, slitting and sheeting. The optimal solution for high productivity.

TOP-330-PLUS	OPTION WIDTH 420MM/520MM
Max Web Width	330 mm
Max Die-cutting Speed (full-rotary)	110 m/min
Max Die-cutting Speed (semi-rotary)	60 m/min
Max Flexo Printing Speed	110 m/min
Accuracy of Flexo Register	±0.15 mm
Max Unwinder dia.	700 mm
Max Rewinder dia.	700 mm
Min Slitting width	16 mm
Accuracy of Adhesive Cutting	±0.15 mm
Accuracy of IML Cutting	±0.25 mm
Standard Magnetic Cylinder	120 T
Total Motor Power	19 KW ~ 21 KW
Registration	Mark Sensor
Dimension	3600 × 1260 × 1925 mm
Weight	3500 KGS



UNWINDER & WEB GUIDING

Unwinder with closed-loop tension control. Electronic web guide with ultrasonic edge guide sensor. 76 mm air expanding mandrel. Max diameter 700 mm - 1000 mm roll capacity.

FLEXO PRINTING UNIT

Independent, servo-driven full rotary printing unit with auto pre-positioning and registration. Offers reverse side printing. Printing repeat lengths of 50 mm - 457 mm.



SEMI- OR FULL ROTARY DIE CUTTING

Independent and servo-driven. Repeat lengths from 50 mm - 330 mm for semi-rotary, and 190.5 mm - 476.25 mm for full rotary. Magnetic or solid/engraved cylinders.



*Cost-efficient
high quality
varnishing
& die cutting*

COLD FOIL & SUPER VARNISH

Cold-foil and super varnish with two pneumatic shafts and unwind/rewind.



*The optimal
solution
for high
productivity*

IML SYSTEM

IML die-cutting system designed for easy installation and removal. Static eliminator in label output collection table works with counter and stepless speed regulation.



REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 700 mm maximum rewind diameter.