


WON-330 / SLITTER REWINDER



The WON-330 narrow-web slitter rewinder is fully servo-driven and features taper tension control, top brand web guiding, turret rewind, meter and number counting, static eliminator etc. The ultimate configuration for high productivity and quality.



WON-330

AVAILABLE WIDTH: 330MM/450MM/520MM

	S330	S450	S520
Max Web Width	330mm	450mm	520mm
Max Speed	300m/min	300m/min	300m/min
Min Slit width	16mm	16mm	16mm
Max Unwinder dia.	700mm	700mm	700mm
Max Rewinder dia.	400mm	400mm	400mm
Blades Installed	6 Sets	6 Sets	6 Sets
Air Supply	0.4~0.6MPa	0.4~0.6MPa	0.4~0.6MPa
Power Supply	3 PH+N+PE	3 PH+N+PE	3 PH+N+PE
Total Motor Power	7KW	7KW	10KW
Dimension	1800×1200×1400mm	1800×1320×1400mm	2265×1390×1400mm
Weight	1200KGS	1300KGS	1550KGS



UNWINDER & WEB GUIDING

Servo driven unwind for clock wise and anti-clock wise unwinding. Automatic tension control, end-of-roll detection, webguide, integrated splice table, 76mm unwind mandrel. Factory upgrade to unwind rolls with dia = 1000mm and a reel lift possible.

TURRET REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 400mm maximum rewind diameter.



COUNTER

High-quality German-made counting sensor - extra accessories needed for transparent film material.



SLITTING OPTIONS

Optional standard 6 shear slitter or razor blade slitter. Easy to install. Features a standard high pressure waste suction system.



Fully
Servo-Driven
Narrow-Web
Slitter
Rewinder

* May vary depending on selected options&configurations